

## Bon Jour 45

Ceiling Recessed Fixed Downlight

### Description

LED luminaire for recessed mounting into plasterboard ceilings.

Once installed, the luminaire edge projects from of the ceiling 0.39" creating a unique and very refined aesthetic effect. The luminaire's body is injection molded aluminium.

It is available in three sizes: Bon Jour 45 (Ø 1.77"), 90 (Ø 3.54") and 145 (Ø 5.71"). Reflector made of anodized gloss aluminium with diffuser element made of polycarbonate. Available finishes: white, copper and black.



### Lamps

POWER LED: CREE  
 6W, 575lm, 2700K, CRI 90  
 6W, 615lm, 3000K, CRI 90

Delivered lumens from 153lm up to 392lm

### Construction

Luminaire body made of die cast aluminium.

Reflector made of anodized gloss aluminium with diffuser element made of polycarbonate.

Honeycomb and cross screening cylinder included.

Factory suggest 5" minimum plenum height.

### Electrical

Fixture is constant current, low voltage LED

Fixture is 6 watts

### Finish

01 White    CU Copper    14 Black



### Notes

Embedded luminaire for LED light source.

Class II Remote power supply 120/277V not included, order separately.

Beam angle is 24°




Listings: UL Listed, IP44 damp location.

### Warranty

2 years from date of sale.

### Photometrics

For current IES files please visit [architectural.flosusa.com](http://architectural.flosusa.com)



### How to Specify



ex. 03.2001.14.9S

QTY	Item Number	Beam Angle	Description	Finish	Power Supply
	03.2001	25°	Bon Jour 45, 6W, 575lm, 2700K, CRI 90	<input type="checkbox"/> 01 = White <input checked="" type="checkbox"/> 14 = Black <input type="checkbox"/> CU = Cooper	9S = Class II Remote power Supply, order separately
	03.2006	25°	Bon Jour 45, 6W, 615lm, 3000K, CRI 90	<input type="checkbox"/> 01 = White <input checked="" type="checkbox"/> 14 = Black <input type="checkbox"/> CU = Cooper	9S = Class II Remote power Supply, order separately

**Bon Jour 45**

Ceiling Recessed Fixed Downlight

**Required Accessories**

Image	QTY	Item Number	Description
		SP40W500MA-10V-A02	Splice Box UL 7"x3-5/8"x1-1/4", UL. With Driver Programmed to 500mA , 40W, 0-10V Dimmable, 120/277V.
		SP25W500MA-10V-A02	Splice Box UL 7"x3-5/8"x1-1/4", UL. With Driver Programmed to 500mA , 25W, 0-10V Dimmable, 120-277V / Required for Canada