




The Tracking Magnet EVO
High-tech LED lighting system for interior architecture

Spot 50 How to specify 03.8033.40.DA

Accent LED Spot modules can be rapidly exchanged and repositioned without tools. Light elements are quick to position and connect automatically with magnets. Honeycomb and cross baffle comes standard with the fixture. IP20.



| CCT | CRI | Initial Lumens | Delivered Lumens | Watts | Beam Spread | Part Number | Finish | Dimming Protocol | Photometric | | | | | | | | | | | | |
|------|-----------|----------------|------------------|-------|-------------|-------------|--|--|--|------|------|---|-----------|---|----------|---|----------|---|---------|---|---------|
| 3000 | 90 | 307 | 212 | 3.5 | 26° | 03.8033 | <input type="checkbox"/> 40 = White <input type="checkbox"/> 14 = Black <input type="checkbox"/> 05 = Chrome | Dimmable on Board 1V = 0-10V, 10% Dimming DA = DALI, 10% Dimming | <table border="1"> <thead> <tr> <th>E(h)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1012 0.47</td> </tr> <tr> <td>2</td> <td>253 0.94</td> </tr> <tr> <td>3</td> <td>112 1.41</td> </tr> <tr> <td>4</td> <td>63 1.88</td> </tr> <tr> <td>5</td> <td>40 2.35</td> </tr> </tbody> </table> Luminous flux luminaire 212 lm | E(h) | D(m) | 1 | 1012 0.47 | 2 | 253 0.94 | 3 | 112 1.41 | 4 | 63 1.88 | 5 | 40 2.35 |
| E(h) | D(m) | | | | | | | | | | | | | | | | | | | | |
| 1 | 1012 0.47 | | | | | | | | | | | | | | | | | | | | |
| 2 | 253 0.94 | | | | | | | | | | | | | | | | | | | | |
| 3 | 112 1.41 | | | | | | | | | | | | | | | | | | | | |
| 4 | 63 1.88 | | | | | | | | | | | | | | | | | | | | |
| 5 | 40 2.35 | | | | | | | | | | | | | | | | | | | | |
| 2700 | 90 | 286 | 205 | 3.5 | 26° | 03.8032 | | | <table border="1"> <thead> <tr> <th>E(h)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>977 0.47</td> </tr> <tr> <td>2</td> <td>244 0.94</td> </tr> <tr> <td>3</td> <td>109 1.41</td> </tr> <tr> <td>4</td> <td>61 1.88</td> </tr> <tr> <td>5</td> <td>39 2.35</td> </tr> </tbody> </table> Luminous flux luminaire 205 lm | E(h) | D(m) | 1 | 977 0.47 | 2 | 244 0.94 | 3 | 109 1.41 | 4 | 61 1.88 | 5 | 39 2.35 |
| E(h) | D(m) | | | | | | | | | | | | | | | | | | | | |
| 1 | 977 0.47 | | | | | | | | | | | | | | | | | | | | |
| 2 | 244 0.94 | | | | | | | | | | | | | | | | | | | | |
| 3 | 109 1.41 | | | | | | | | | | | | | | | | | | | | |
| 4 | 61 1.88 | | | | | | | | | | | | | | | | | | | | |
| 5 | 39 2.35 | | | | | | | | | | | | | | | | | | | | |